

# Portable Power GK-2000



- 2000W
- 1997Wh
- LiFePo4
- AC Input 1100W
- MPPT Input 500W



Over-charge protection



Over-temperature protection



Over-voltage protection




Short-circuit protection



Over-current protection



DC auto-sleep



Pure sine wave



Long life span

## Model:

Capacity:	1997Wh
TYPE-C Output:	100Wmax*1/ 20Wmax*3
AC charging:	50/60HZ 1100Wmax
AC output:	Rated 2000W,Peak 4000W
MPPT input:	11.5-50V20A below 500Wmax
USB:	USB-A(5V2.4A)*2
DC5521:	12V/3A*2
Cigar lighter output:	12V/10A
Cell:	LiFePo4
Operation temperature:	-10-40 °C
Charging temperature:	0-40 °C
Weight:	22kg
Size:	392*279*323mm
AC Waveform:	Pure Sine Wave



Fully Charged in 2 Hours Via AC only



Fully Charged in 4-5 Hours Via your solar only



Capable to Charge 12 Devices Simultaneously



95% Inverter Efficiency



95% of DOD (Depth of Discharge)



V0 Level of Fire protection materials



UL certified LFP cell to supply long life span



PD100 support PD 3.0, QC 3.0, FCP, AFC, Apple 2.4A

sales@dowellelectronic.com

www.dowellelectronic.com